

*LCD display*

# 3 PHASE ROTATION TESTER

Model : RT-616

*ISO-9001, CE, IEC1010*



**LUTRON ELECTRONIC**

*The Art of Measurement*

# *LCD display*

## 3 PHASE ROTATION TESTER

### Model : RT-616


#### FEATURES

- \* Electronic ( not mechanical ) rotation test, high reliability.
- \* LCD display, easy ready and simple operation.
- \* Signal input voltage : 100V AC up to 660V AC max.


#### GENERAL SPECIFICATIONS

Signal Input Voltage	100V AC up to 660 AC maximum, 3 min. limit for over 500V AC.
Signal Current	Approx. 7 mA per phase.
Consumption	
Signal Freq.	45 to 70 Hz.
Range	
Circuit	* Electronic ( not mechanical ). * Custom one-chip of microprocessor LSI circuit.
Power Supply	DC 9V battery. 006P, MN1604 ( PP3 ) or equivalent. Approx.
Power Consumption	Approx. DC 8 mA.
Operating Temperature	0 to 50 °C ( 32 to 122 °F ).
Operating Humidity	Less than 80% RH.
Dimension	100 x 50 x 25 mm. 3.9 x 1.9 x 1.0 inch.
Weight	150 g/0.33 lb.
Standard Accessories	* Operational manual.....1 PC * Meter with 3 PCs 40 cm length test lead and banana Plug.....1 SET * Alligator clip.....3 PC

#### Clockwise ( correct )




#### Counter clockwise ( correct )




#### Line is no connection ( Incorrect )


L1 missing




L2 missing



L3 missing



L1, L2, L3 missing



\* Appearance and specifications listed in this brochure are subject to change without notice.

2208-RT616