

AutoCross-Laser 2 XPG



Green cross-line laser with ultra bright diode technology and additional 5-point laser

- Exact horizontal and vertical alignment of objects
- Good visibility through green laser technology
- Plumb function for synchronous working on floor and ceiling
- Time-saving automatic alignment
- Individually switchable laser lines
- Ideal for work close to the ceiling
- Visual signals indicate when the device is outside its self-levelling range
- GRX-Ready: integrated handheld receiver mode
- Pendulum restraint for safe transport

TECHNICAL SPECIFICATIONS

SELF-LEVELLING RANGE	± 3°
ACCURACY	± 0.2 mm / m
LEVELLING	automatic
VISIBILITY (TYPICAL)*	55 m
WORKING RANGE WITH HAND RECEIVER	(depends on how the technology affects the difference in brightness) 60 m
LASER WAVELENGTH	515 nm
LASER CLASS	2 / < 1 mW (EN 60825-1:2014/AC:2017)
POWER SOURCE	4 x 1.5V LR6 (AA)
OPERATING TIME	approx. 3.5 hours
OPERATING CONDITIONS	0°C ... 45°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
STORAGE CONDITIONS	-10°C ... 70°C, max. humidity 80% rH
DIMENSIONS (W X H X D)	70 mm x 105 mm x 130 mm
WEIGHT	550 g (incl. batteries)