
## Laserliner

## VideoFlex G3 Ultra





This professional video inspection system is suitable for easy visual inspection of hard-to-reach places in pipes, cavities, shafts, masonry and motor vehicles. The small, waterproof camera head and the extremely long, flexible cable ensure the device is suitable for a wide range of applications over very long distances. Illumination with four high-performance LEDs provides clear pictures, even in extremely poor light. Rotation and mirroring ensure the image is always appropriately displayed on the monitor. The inspection results can be saved on an SDHC memory card for evaluation and documentation.



- · Small camera head, ideal for places that are hard to reach
- · Extremely long flexible cable for use over very long distances
- Clear images even under the worst conditions thanks to LED lighting
- Waterproof camera head and cable
- Versatile application due to interchangeable camera head
- 4 high-performance LEDs for powerful object lighting at the camera
- . The images can be stored for evaluation and documentation

| TECHNICAL SPECIFICATIONS |  |
|--------------------------|--|
| CAMERA TYPE              | CMOS image sensor                                    |
| CAMERA HEAD              | ø 9 mm   |
| CAMERA HEAD              | IP 68 (immersion depth 2 m, 60                       |
| PROTECTION CLASS         | min.)  |
| CAMERA RESOLUTION        | 640 x 480 pixels                                     |
| FIELD OF VIEW (FOV)      | 53°  |
| CAMERA FOCUS             | F1 cm - F6 cm  |
| SCREEN TYPE              | 3,5" Colour TFT                                      |
| DISPLAY RESOLUTION       | 320 x 240 pixels                                     |
| IMAGE FORMAT / VIDEO     | JPEG   |
| FORMAT                   | AVI  |
| IMAGE / VIDEO            | 720 x 480 pixels                                     |
| RESOLUTION               |  |
| LENGTH OF FLEX CABLE     | 10 m   |
| LED                      | 10 brightness levels                                 |
| ZOOM                     | 1.5x digital zoom in 10%                             |
|                          | increments   |
| MEMORY                   | Supports up to max. 8 GB SDHC card                   |
| PORT                     | Mini USB   |
| PORTS                    | Micro-SD   |
|                          | Analog-video   |
| POWER SUPPLY             | Li-ion battery pack 3.7V / 1.7Ah                     |
| DIMENSIONS (W X H X D)   | 100 mm x 200 mm x 130 mm x (without flexible tubing) |
| WEIGHT                   | 1600 g (incl. battery pack and flexible tubing)      |
|                          |  |



