

WINDOW TINT METER



(The WTM-1500P supports printing)

Features

- * Simple operation, fast measurement speed, good sensitivity, high measurement accuracy
- * WTM-1500P can be connected to a printer to print test data
- * Instrument startup automatic calibration and manual calibration
- * Large capacity storage, can store 500 measurement data

Specifications

Measurement range	0.0%-100%
Measurement quantity	% beam transmission
Thickness of the object to be measured	<30mm
Volume of the measured object	<10mm*10mm
Shutdown mode	Automatic shutdown or manual shutdown can be set
Backlight	LED backlight
Resolution	0.1%
Host size	75mm*135mm*25mm
Probe size	Φ37mm*136mm
Power	4 * 7 batteries
Operating temperature	0°C-40°C
operating humidity	< 85%
Wavelength range	380nm-780nm

产品型号: WTM-1500
WTM1-1500P

Application

Field measurement for automobile manufacturing and testing, glass products, aerospace and other industries. Measurement of transmittance of protective film, PC, acrylic and other plastic products. Other transparent or semitransparent material transmittance measurement. (Note: printed, frosted and milky materials are not suitable for measurement by this machine)

parts list

Standard Accessories (WTM-1500P)	host (built-in Bluetooth module)
	Bluetooth printer
	a roll of thermal paper
	packaging box
Optional Accessories (WTM-1500)	manual
	host
	packagingbox
	manual